



2ME


1. Dimensions / Weight




2ME-CFP
weight: 10.40 kg




2ME-4L
weight: 8.20 kg



2ME-BL TS25 ARM-BL
weight: 12.80 kg



2ME-BL ST53-POL ARM-CR
weight: 12.60 kg



SEAT – 2ME CFP / 2ME 4L



SEAT 2ME S 4L

2. Materials / Versions

2.1. Base / Frame

2.1.1. Conference swivel chairs

Bases:

- Ø 710 mm five-star black polyamide (TS25),
- Ø 710 mm five-star white polyamide (TS25-W),
- Ø 700 mm five-star aluminium powder-coated in White aluminium RAL 9006 colour (ST44-WA),
- Ø 700 mm five-star polished aluminium with chrome effect (ST44-POL),
- Ø 740 mm four-star polished aluminium with chrome effect (ST53-POL).

2.1.2. Conference frame chairs

Cantilever frame – made of steel tube
Ø 22 × 3 mm.

4-leg frame – made of steel tube Ø 22 × 2 mm.

Finish options:

- powder-coated in Traffic white RAL 9016 colour (W),
- powder-coated in Jet black RAL 9005 colour (BL),
- powder-coated in White aluminium RAL 9006 colour (WA),
- or „Fashion Collection“ colour,
- chromium plated (CR).

Stacking:

Cantilever chair – stacking up to 3 pieces.

4-leg chair (2ME-S only) – stacking up to 2 pieces.

2.2. Castors / Glides

2.2.1. Conference swivel chairs

Five-star base

Ø 65 mm black plastic self-braking castors for soft

floors (ESH) as standard, or hard floors (ESHH) as an option.

Ø 65 mm ring castors for soft floors (ESHR) or hard floors (ESHHR) – both as an option.

Four-star base

Glides for soft floors (GB) as standard, or hard floors (GBF) as an option.

2.2.2. Conference frame chairs

Cantilever frame

Glides for soft floors (GB) as standard, or hard floors (GBF) as an option.

Mini-glides for soft floors (GBMF), or hard floors (GBM) – both as an option.

Frame without glides (NGB) – as an option.

4-leg frame

Self-leveling glides for soft floors (GBP) as standard, or hard floors (GBPF) as an option.

Mini-rolls for soft floors (RMH), or hard floors (RMHH) – both as an option.

2.3. Mechanisms

TILT/AR mechanism

– tilting of integrated seat and backrest in the range of 11° (free-floating),

– smooth height adjustment of chair with pneumatic gas lift.

2.4. Seat and backrest

Seat

Structure is made of 6-layer plywood, thickness approx. 9 mm covered with 2-layers of foam, thickness 15 mm, density 40 kg/m³, and thickness 16 mm, density 35 kg/m³.

Seat cover is made of black or white polypropylene (PP), according to selected colour concept.

Backrest

Upholstered backrest – structure is made of 6-layer plywood, thickness approx. 9 mm covered in front part with foam thickness 20 mm, density 25 kg/m³, and back part with foam thickness 6 mm, density 35 kg/m³.

3. Armrests

Fixed armrests – made of glass fiber reinforced polyamide (PA + GF) in black or white colour.

4. Packaging

Conference frame chairs

- conference swivel – 1 piece per box (fully assembled),
- conference cantilever frame – 2 pieces per box (fully assembled),
- conference 4-leg frame – 1 piece per box (fully assembled),
- 4-leg S (stackable) – 2 pieces per box (fully assembled).

5. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

GS Safety Certificate.

REMODEX (durability certificate) – approvals compliant with EN 1335 and EN 1022.