

lani

7060.01 - 7060.56



binder

upholstery 02

descripción

diseño resistente de lana afelpada en colores modernos combinables

composición

80% lana / 20% poliamida

ancho

± 140 cm, ± 55 inches

peso

± 640 gr/m¹, ± 21 oz/yd¹ fabrics

combustión retardada

EN 1021/ 1-2

BS 5852, crib 5 with FR finish

DIN 4102, B2 with FR finish

UNI VF 9175, clase 1 IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

NF D 60-013 - AM18

resistencia al desgaste

ISO 12947-2

>300.000 rubs martindale

ASTM D4157

100.000 double rubs wyzenbeek

pilling

ISO 12945-2

4 (escala 1-5)

ASTM D3511

1 (escala 1-5)

resistencia al frotamiento

ISO 105-X12

wet 4 - 5 / dry 4 - 5 (escala 1-5)

AATCC 8

wet 5 / dry 5 (escala 1-5)

insensibilidad a la luz

ISO 105-B02

5-7 (escala 1-8)

AATCC 16.3: 40 hours

3.5 (escala 1-5)

resistencia al deslizamiento de costuras

ISO 13936 - 2

lizo 2.6 mm / trama 3 mm

ASTM D4034

lizo 125 lbs / trama 116 lbs

resistencia a la tensión

ASTM D5034

warp 206 lbs / weft 202 lbs

mantenimiento





lani

7060.01 - 7060.56

