

# marmoleum® decibel 18 dB



Marmoleum Decibel is 3.5mm thick and provides an impact sound reduction of 18dB. The acoustic performance is achieved by laminating 2.5mm Marmoleum onto a 1mm thick layer of polyolefin foam.

Marmoleum Decibel is also available in all Marmoleum colours as a made-to-order item with an 18dB impact sound rating. Please note that minimum order quantities and lead times will apply. Please contact Forbo Customer Service for more details.

Description	Linoleum sheet	
Dimensions	EN-ISO 24341	Roll width 2.0m Roll length ≤ 32m
Total thickness	ISO 1765	3.5mm
Collection size	27	
Application	EN 1307	Class 23/33/41
Acoustical impact noise reduction	≤ 17 dB	
CE	EN 14041	
Reaction to fire	ISO 9239-1	CRF >4.5kw/m <sup>2</sup> Smk Dvlp <750%.min
Slip resistance	AS 4586:2013	R10

Our recommended adhesive is 540 Eurosafe Special or 640 Eurostar Special. Full technical specifications are available at: [www.forbo-flooring.com.au/downloads](http://www.forbo-flooring.com.au/downloads)



386035   silver shadow LRV 48	372435   orbit LRV 37	371135   cloudy sand LRV 49	312035   rosato LRV 51		
262135   dove grey LRV 36	370835   fossil LRV 34	325235   sparrow LRV 29	303835   Caribbean LRV 55	322535   dandelion LRV 48	
314635   serene grey LRV 27	370635   beton LRV 28	324635   shrike LRV 21	305335   dove blue LRV 23	374135   yellow glow LRV 58	373835   orange glow LRV 27
304835   graphite LRV 14	372335   nebula LRV 17	370935   silt LRV 22	373935   blue glow LRV 16	374235   green glow LRV 39	374335   red glow LRV 14
387235   volcanic ash LRV 10	370735   black hole LRV 7	356835   delta lace LRV 13	303035   blue LRV 12	322435   chartreuse LRV 38	312735   Bleekerstreet LRV 9